

Technical Data

MULTIGRIP

Type	Excavators up to (t)	Dead weight ca.* (kg)	Capacity SAE (litres)	Cutting width (mm)	Opening (A) max.(mm)
MG.015.050	1.5	55	33	500	340
MG.022.055	2.2	80	53	550	530
MG.030.060	3	150	78	600	730
MG.045.060	4.5	165	114	600	825
MG.060.060	6	185	150	600	1,010
MG.075.080	7.5	250	237	800	1,115
MG.095.080	9.5	345	252	800	1,200
MG.120.080	12	380	280	800	1,300
MG.150.100	15	670	524	1,000	1540
MG.190.100	19	730	689	1,000	1,620
MG.220.100	22	850	779	1,000	1,690
MG.250.100	25	970	895	1,000	1,750

* All weight specifications incl. mounting plate, suitable for Lehnhoff / Available for excavators ranging from 0.8t - 25t • other cutting widths on request

PROFILÖFFEL

Type	Excavators up to (t)	Dead weight ca.* (kg)	Capacity SAE (litres)	Cutting width (mm)	Back width (mm)
PL.010.080	1.8	64	95	800	400
PL.020.090	2.5	93	120	900	500
PL.040.110	4	130	130	1,100	680
PL.060.120	6	170	200	1,200	740
PL.080.140	10	290	340	1,400	800
PL.120.150	12	390	450	1,500	900
PL.140.170	16	510	665	1,700	1,100
PL.220.160	25	805	1,160	1,600	1,000

* weight incl. mounting plate, suitable for Lehnhoff

VARIOLÖFFEL

Type	Excavators up to (t)	Dead weight ca.* (kg)	Capacity SAE (litres)	Slope angle	Radius (mm) trench bottom
VarioLöffel without RotoTop					
VL 112.100	2 - 3.5	140 *	120	54°	150
VL 112.200	3 - 6.0	190 *	200	54°	150
VL 112.300	4.5 - 8.5	240 *	300	54°	150
VL 112.400	7 - 14	320 *	400	54°	150
VL 112.700	14 - 25	570 *	700	54°	150

VarioLöffel with RotoTop					
VL 112.220	3 - 6.0	310 **	200	54°	150
VL 112.320	4.5 - 8.5	340 **	300	54°	150
VL 112.421	7 - 14	460 **	400	54°	150
VL 112.722	14 - 25	750 **	700	54°	150

* Weight specifications incl. mounting bracket, suitable for Lehnhoff ** Weight specifications when directly mounted to the bucket

BANKETLÖFFEL

Type	Excavators up to (t)	Dead weight ca.* (kg)	Capacity SAE (litres) incl. cover	Cutting width (mm)	Height (mm) total/banquet
BL.100.120	10	125	300	1,200	480/300
BL.145.140	15	206	700	1,400	610/300

* Weight specifications incl. mounting plate, suitable for Lehnhoff

CUTWHEEL

Type	Excavators up to (t)	Dead weight ca.* (kg)	Cutting width (mm)	Cutting height above ground (mm)	Oil quantity Oil pressure
CW.149.123	15	650	1230	150	80-90 L/min 180-200 bar
CW.099.099	10	500	990	130	40-45 L/min 180-200 bar

* Weight specifications incl. mounting plate, suitable for Lehnhoff

KRANFIX

Type	Quick-coupler 1	For attachment to e.g.:	Dead weight ca.
SW 351.001	Quick-coupler , swinging width 80 mm	Loglift, EPSILON alt	35 kg
SW 352.001	Quick-coupler , swinging width 99 mm	Loglift von F61-F121	36 kg
SW 359.004	Quick-coupler for Epsilon swing incl. hydraulic couplings	EPSILON M/S/	39 kg

Type	Changer cartridge 1	For attachment to e.g.:	Dead weight ca.
WK 451.101	Changer cartridge for log grapples or soil grabs with toothed ridge	SW 351/352/359	35 kg
WK 451.102	Changer cartridge with toothed ridge „straight“ for twin grab swing brake with toothed ridge	SW 351/352/359	35 kg
WK 451.201	Changer cartridge for harvester heads incl. bracket for twin grab swing brake	SW 351/352/359	40 kg
WK 459.001	Changer cartridge for log grapple without toothed ridge	SW 359	39 kg

Type	Quick-coupler linkage 1	For attachment to e.g.:	Dead weight ca.
SK 951.102	Long, angulated for VarioLöffel, mulcher etc.	SW 351/352/359	135 kg
SK 951.301	Short, straight for mulchers etc	SW 359	85 kg

QUICKON

Type	Dead weight ca. (kg)	Coupling sizes (inch)	Note
QO.021.011	3	3/4 - 1 1/4	Couplings are centred in gripping shells
QO.021.011 incl. gripping adapter	3	1/4 - 3/4	Taken up with gripping adapter on screw connection